



LE-PRO 200 (floor model)  
with optional TDS Blending Valve

Designed to offer a feature-rich solution for many residential and light commercial applications. Engineered with the latest in membrane technology for increased efficiency and high-performance properties. This compact system is available as a stand-alone floor model, or wall mountable.

### STANDARD FEATURES

- Sediment/Carbon Pre-Filtration
- Carbon Post-Filtration
- Pentek® 10" Slim Line Housings
- Product Water Pressure Shutoff Switch
- Pre-Filter Pressure Gauge, 0-100 PSI
- Post-Filter Pressure Gauge, 0-100 PSI
- Pump Pressure Gauge, 0-200 PSI
- Product Water Pressure Gauge, 0-100 PSI
- Pentek® Twist-to-Lock Membrane Housing
- Aquatec® High Flow Booster Pump
- Aquatec® Feed Water Solenoid Valve
- Aquatec® Auto Flush Timer Valve
- JG® Fittings and Tubing with Safety Locking Clips
- Factory Tested and Inspected for Top-Quality
- Designed and Assembled in the U.S.A.
- One Year Limited Warranty

ITEM NUMBER	MODEL	CAPACITY (GPD/GPM)	ELECTRICAL*	MEMBRANE QUANTITY	DESIGN RECOVERY	NOMINAL TDS REJECTION
8772001	LE-PRO 200	200 / 0.14	115-120VAC, 60HZ	1	40%	98%
8773001	LE-PRO 300	300 / 0.21	115-120VAC, 60HZ	2	50%	98%

\*230VAC, 50HZ SYSTEMS ALSO AVAILABLE

MOUNTING STYLE	
878881	Floor Standing Bracket Kit
878880	Wall Mounting Bracket Kit

### OPTIONAL FEATURES

**TDS Monitor, Dual Probe:** Better monitor the performance of your membrane to know when to service or replace.

**TDS Blending Valve:** Incorporates a micro needle valve for a controlled blend of filtered feed water into the product water stream for more selective TDS.

**Specialty Post Filter Cartridge:** Substitute the Carbon Post-Filter for a Calcite cartridge to help raise pH levels and re-mineralize the product water. Or use with a DI cartridge to further reduce TDS.

**20" Filter Housings:** Provides additional pre/post treatment for extended protection. Only available on Wall Mount Models.