# **Model 1500**

# .75" Residential Control Valve



#### **Features**

- · Fully adjustable, 5-cycle control delivers upflow backwash, downflow brining, slow rinse, rapid rinse, brine refill, and downflow service
- · Time-tested, hydraulically balanced piston, seal and spacer concept to pilot service flow and regeneration
- · Solid, lead-free brass valve body
- · Continuous flow rate of 17 GPM
- · Backwash capacity handles tanks up to 14" in diameter for softener applications, and 10" in diameter for filter applications
- Both English and Spanish languages on the label

# **Options**

- Hot water up to 180°F for filters and non-metered control valves
- Hot water up to 150°F for any metered control valves
- · Service valve operator
- · Side mount
- · No hard water bypass
- · Environmental cover
- · Nickel plating
- · Auxiliary switches
- · Manual operation (filter or softener)
- · Choice of 7 or 12 day clock
- · Meter delayed or immediate initiated regeneration
- · Filter or softener control valves

Va	lν	e S	Sp	ec	ifi	ca	tic	วท	S

Valve material	Lead-free brass*		
Inlet/Outlet	3/4" NPTF		
Cycles	5		

## Flow Rates (50 psi Inlet) - Valve Alone

Continuous (15 psi drop)	17 GPM
Peak (25 psi drop)	22 GPM
Cv (flow at 1 psi drop)	4.8
Max. backwash (25 psi drop)	14 GPM

### Regeneration

Downflow/Upflow	Downflow only			
Adjustable cycles	Yes			
Time available	Electromechanical: 164 minutes			

#### **Meter Information**

Meter accuracy	.25 - 15 GPM +/- 5%			
Motor conscity range (gal.)	Standard: 125 - 2,125			
Meter capacity range (gal.)	Extended: 625 - 10.625			

#### **Dimensions**

Distributor pilot	13/16" O.D.		
Drain line	1/2" Quick Connect		
Injector brine system	1600		
Brine line	3/8"		
Mounting base	2-1/2" - 8 NPSM side mount 3/4" NPTF 6 - 12"		
Height from top of tank	6 - 12"		

# **Typical Applications**

Water softener	6" - 14" diameter		
Filter	8" - 10" diameter		

#### **Additional Information**

Electrical rating	24 v, 110 v, 220 v - 50 Hz, 60 Hz		
Estimated shipping weight	Time clock: 11 lbs.		
Pressure	Hydrostatic: 300 psi Working: 20 - 125 psi		
Temperature	34° - 110° F		

<sup>\*</sup> As defined in the U.S. EPA Safe Drinking Water Act