

REO-FLEX POLYETHYLENE TUBING

Features:

- ◆ Flexible and lightweight
- ◆ Low-density, FDA grade polyethylene material
- ◆ Colors available: Black and Natural
- ◆ Sizes available (OD): 1/4", 3/8", 1/2", 5/8", 3/4"
- ◆ Chemical resistant
- ◆ Operating temperature range: -5°F to 125°F

Ideal Applications:

- ◆ Softener brine line
- ◆ Softener drain line
- ◆ Low pressure feed line

Part #	Color	O.D.	I.D.	Working psi @ 70°F	Coil Length
5925001	Natural	1/4"	.170"	135 psi	100'
5925003	Black	1/4"	.170"	135 psi	100'
5938001	Natural	3/8"	1/4"	120 psi	100'
5938003	Black	3/8"	1/4"	120 psi	100'
5912001	Natural	1/2"	3/8"	90 psi	100'
5912003	Black	1/2"	3/8"	90 psi	100'
5958001	Natural	5/8"	1/2"	70 psi	100'
5958003	Black	5/8"	1/2"	70 psi	100'
593401	Natural	3/4"	5/8"	60 psi	100'
593403	Black	3/4"	5/8"	60 psi	100'

Note: As temperature increases, the working pressure decreases.

