



ICF/ISF SERIES Inline Filters



- Sediment and coconut shell carbon
- 1/4", 3/8" Female NPT and quick connections
- Superior spring design to minimize channeling

HYDRONIX ICF/ISF FILTER HOUSINGS

Utilize NSF listed coconut shell GAC and are designed to remove unpleasant taste and odor and reduce sediment to produce cleaner, clearer, better tasting water. Hydronix ICF Series Granular Activated Carbon Filters are easily installed on the water line to an automatic ice maker, Reverse Osmosis System or water dispensing system.



ICF-10



ISF-10

Chlorine Taste & Odor Reduction		
Coconut Shell Carbon		
Service Life	1 yr or 2000 gal (7570 L)	
Maximum Flow	.50 GPM (1.9 LPM)	
Maximum Pressure	125 PSI (8.6 BAR)	
Maximum Temperature	100°F (38°C)	
Minimum Temperature	35°F (2°C)	
Micron Rating	5M	

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Dirt & Sand Reduction	
Service Life:	Applications vary
Maximum Flow:	.50 GPM (1.9 GPM)
Maximum Pressure:	125 PSI (8.6 BAR)
Maximum Temp:	100°F (38°C)
Minimum Temp:	35°F (2°C)
Micron Rating:	5M

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

2" DIAMETER SPECIFICATIONS	
Part Number	Description
ICF-6	Hydronix Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" FNPT
ICF-6Q	Hydronix Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" Hydrofit™ QC
ICF-10	Hydronix Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" FNPT
ICF-10Q	Hydronix Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" Hydrofit™ QC
ISF-10	Hydronix Inline Sediment Filter: 2"x 10", 1/4" FNPT

2.5" DIAMETER SPECIFICATIONS	
Part Number	Description
ICF-2512	Hydronix Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" FNPT
ISF-2512	Hydronix Inline Sediment Filter: 2.5" x 12", 1/4" FNPT

Applications

- Ice makers
- Reverse osmosis systems
- Water Coolers
- Coffee makers

ICF/ISF SERIES

Inline Filters

Refrigerators

Available Port Sizes

- 1/4" Female NPT Basic
- 3/8" Female NPT Basic
- 1/4" Quick Connect
- 3/8" Quick Connect